

# Heating Room Thermostat

HTW-31-KT13V

This surface-mounted heating thermostat has been developed to be able to switch electric and conventional heating systems on and off using a set temperature and time.



## Functions

---

- ✓ Large display can be clearly read with the background lighting.
- ✓ Easy to fit thermostat and receiver.
- ✓ Knob Button make it easy to use, press button to on/off thermostat, turn left/right to adjust the values.
- ✓ Non-programmable
- ✓ White Backlight
- ✓ The display shows the set temperature as well as the measured temperature.
- ✓ Temperature display in degrees Celsius.

## Technical Data


---

Thermostat operating voltage:	2 x AAA1.5 V, alkaline batteries.
Backup storage:	EEPROM
Maximum voltage / (ohmic) load:	8A.
Switch contacts:	NO and NC.
Temperature settings:	5°C ~ 30°C, 0.5°C increments.
Accuracy:	+/- 0.5°C
Thermostat dimensions:	Surface mounted, 135mm x 87.5 mm x 23.2mm.
Color:	White
IP protection rating:	20.

# Heating Room Thermostat


HTW-31-KT13V

## Temp. Calibration & Channel Pairing



Temp. Calibration: Turn off thermostat, press On/off button for 3 sec. to calibrate Temp. by pressing “+” and “-” buttons.

## Wiring Diagram



## Dimensions

Unit

